



## JCB TELEHANDLER

## THE VERSATILITY THAT SUCCESS DEMANDS.





Maximum lift capacity up to 4000 Kg\*.



Q-Fit mechanism for quick change of attachment.



360° Hi-Viz global cabin design with ROPS & FOPS.



New LiveLink 4.0 for better 24x7 monitoring.



## **SPECIFICATION: TELEHANDLER**

Specifications	530-110	530-70	540-70
Engine	JCB 444 TCIC, 4 Cylinder, 4.4 L 55 kW (74 hp) Max torque 400 Nm		
Transmission	JCB shyncroshuttle transmission, smooth shift gear box with integral torque convertor and electrically operated reversing shuttle.		
Hydraulic pump flow (lpm) @2200 rpm	108		
Hydraulic Pressure (p.s.i)	3 5 5 3		
Brakes	JCB 'Q' brakes, hydraulically actuated, dual line, self adjusting (compensated), oil immersed, multi-disc type on the rear axle		
Steering	Rear -Wheel hydrostatic power steering with manual capability in the event of engine or hydraulic power failure		
Electrical	130 Ampere-hour 12 Volts battery system with alternator and full road lighting. IP69 electrical conectors		
Tyres	Front: 13.00 x 24 -16PR, Rear 12.5 x18-12 PR, Tyre option -HD tyre, Extra HD tyre /Solid tyre /Agri tyre		
Wheelbase (m)	2.54		
Operating weight (kg)	9060	7154	8600
Maximum lift capacity (kg)	3 000	3000	4000
Lift capacity to full height	3000*	2500	2500
Lift capacity to full reach	I 400	1210	I 500
Lift Height (m)	П	7	7.02
Maximum forward reach (m)	7.40	3.83	3.84
Reach with 1 ton load (m)	7.46		
Placing height (m)	10.5	6.3	6.5

\*With stabilisers extended

## **EXCEEDING EXPECTATIONS EVERYWHERE**



₿6000+ Trained service engineers

20<sup>+</sup> Operator Training centres











Extended Warranty Programme for your peace of mind. Plus JCB Care

Track your machine at your fingertips, download from:







All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependent upon the exact specification of machine.

Call us for a demo: 1800-1037-386









Follow us: f 💟 🖸 🧑 in /JCBIndiaLtd

