



YOUR PARTNER IN SUCCESS JCB 3DXxtra BACKHOE LOADER



Xtra Productivity Bigger Bucket: 0.30 cu.m, Higher Hydraulic Flow: 148 LPM



5.05m Dig depth & 2.93m Dump Height with Higher Digging forces



15%^{*} Lower Maintenance Cost with 4000 hours for Hydraulic Change Interval



Innovative Features Easy Shift, Semi-automatic kick down, Digital Display, Auto Idle, Auto Stop, Trip Meter etc.

CO XPERT



LiveLink 4.0 & Intellidignostic for Enhanced Uptime







JCB ENGINE ecomax

Powered by



TOE



SPECIFICATION: 3DX XTRA BACKHOE LOADER

ENGINE

JCB 444,CRDI 55 kW (74 hp) CEV Stage IV Engine, 4 cylinder, water cooled, Turbocharged with EGR Diesel Engine.

TRANSMISSION

Easy Shift JCB synchroshuttle transmission provides effortless gear shifting with column mounted rotating switch. It consists of a 4-speed, fully synchromesh, smooth shift gear box with integral torque convertor.

HYDRAULIC PUMP FLOW

148 LPM @ 2 200 rpm

HYDRAULIC PRESSURE

3625 p.s.i.

BRAKES

JCB 'Q' brakes, hydraulically actuated, dual line, self adjusting (compensated), oil immersed, multi-disc type on the rear axle.

STEERING

Power track steering rod system provides equal turn steering & quick response with less operating force. Working pressure 2 320 p.s.i. (160 bar)

ELECTRICAL

130 Ampere-hour 12 Volts battery system with alternator and full road lighting.

TYRES

Front : 9 x 16 - 16 PR Rear : 16.9 x 28 - 12 PR

SHIPPING WEIGHT

7630 kg

WHEELBASE

2.17 m

STANDARD SHOVEL

1.1 cu.m

STANDARD BUCKET CAPACITY 0.30 cu.m

DUMP HEIGHT

2.93 m

LOAD OVER HEIGHT

3.37 m

MAX. DIG DEPTH

5.05 m

MAX. WORKING HEIGHT 6.01 m

LOADER ARM BREAKOUT FORCE 5 5 16 kgf

BUCKET TEAROUT FORCE 6 186 kgf

EXCEEDING EXPECTATIONS EVERYWHERE



Call us for a demo: 1800-1037-386

Follow us: 📑 💟 🖸 💿 in /JCBIndiaLtd

