

POWERED TO SUCCEED





POWERED WITH UNMATCHED VERSATILITY

IN EVERY TERRAIN 4VVD IS ENGINEERED TO PERFORM UPHILL TASK EFFICIENTLY AND EFFECTIVELY ESPECIALLY IN HILLY TERRAIN.















Perform many jobs with one bucket, introducing the most versatile function of JCB 3DX Super, the 6-in-1 bucket, best suited for road development.













44	
Specifications	3DX Super 4WD
Engine	JCB 444 CRDI, 55 kW (74 hp), TC
Transmission	JCB shyncroshuttle transmission with easy shift 4WD front axle
Hydraulic pump flow (lpm) @2200 rpm	125
Hydraulic pressure (p.s.i.)	3915
Brakes	JCB 'Q' brakes hydraulically actuated, oil immersed, disc type, compensated
Steering	Equal turn, power steering, hydraulic supply from independent steering pump
Electrical	I 30 amph, I2 volts battery with alternator and full road lighting
Tyres	Front: 12.5X18-12PR Rear: 16.9X28-12PR (Industrial) & optional heavy duty tyre
Shipping weight (kg)	8010
Wheelbase (m)	2.24
Shovel size (cu.m)	I. 0 (6 in 1)
Bucket size (cu.m)	0.30
Dump height (m)	2.91
Load over height (m)	3.37
Dig depth (m)	5.05
Max working height (m)	6.01
Loader breakout force (kgf)	5 285
Bucket tearout force (kgf)	5959



EXTENSIVE CUSTOMER SUPPORT NETWORK



Dealer's stamp:

JCB INDIA LIMITED (India Headquarters)

23/7 Mathura Road, Ballabgarh - 121 004 Haryana, India.

For more information, call our toll free no. 1800-1037-386 | Website: www.jcb.com



©2009 JCB Sales. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, photocopying or otherwise, without prior permission from JCB Sales. All references in this publication to operating weights; sizes, capacities and other performance measurements are provided for guidance only and may vary dependant upon the exact specification and usage of machine. They should not therefore be relied upon in relation to suitability for a particular application. Guidance and advice should always be sought from your JCB Dealer. JCB reserves the right to change specifications without notice. Illustrations and specifications shown may include optional equipment and accessories. The JCB logo is a registered trademark of J C Bamford Excavators Ltd.

