





## JCB A45E ARTICULATED BOOM



Compliant with ANSI standard
Anti Crush protection system

1111111

• Auxiliary handrail



- Fully integrated load
- management system
- Function speed control
   4 wheel drive and oscillating axles



- User friendly controls &
  joystick layout
- joystick layoutTouch screen base display
- Full size gate entry

## **Reliability and Durability**




- Electro Deposition Painting (EDP) process
- Rigid Canopies
- Solid Resilient Tyres

Platform Height: 14.7m | Working Height: 16.6m

2

JCB

## SPECIFICATION: ARTICULATED BOOM




DIMENSIONS			
	Weight	kg	7885
А	Width	m	2.26
В	Wheelbase	m	2.03
С	Length (stowed)	m	7.35
D	Height (stowed)	m	2.23
	Tail swing	m	0.12
	Ground clearance	m	0.32
	Wheel loading (per wheel)	kg	1971

PLATE	ORM		
E	Platform length	m	0.85
F	Platform width	m	1.83
	Platform height	m	1.1
	Entry type		Gate
	Entry number		I
	Occupancy		2
	Capacity	kg	250
	Rotation	degrees	160
	Crush protection – electronic		Std


ENGINE	
Make	Kohler
Emissions compliance	EPA T4F
Entry type	Gate
Power kV	V 36
Rated speed rpr	n 2500
Fuel tank capacity	L 59

TYRES	
Туре	Solid Resilient
Size	83.82cm x 31.0 cm (33x12.20)

DRIVELINE		
Drive		4WD
Max stowed speed	km/h	6.5
Max raised speed	km/h	1.1
Gradeability (stowed)	% slope	40



ELECTRICS		
System voltage	$\vee$	12
Battery manufacturer		JCB
Battery model		Powermaster
Capacity	Ah	110
Auxiliary pump system		I 2V DC



 $^{10 m}$  X = Working envelope

LIFT PERFORMANCE		
Max. platform height	m	4.7
Max. working height	m	16.7
Max. outreach	m	8.3
Up and over clearance*	m	7.5
Slew rotation	degrees	355
Wind speed	m/s	12.5
Tilt sensor cut out	degrees	5

 $\ast$  Up and Over clearance is the max height that the basket can reach horizontally



Call us for a demo: 1800-1037-386 Follow us: f 💟 🖸 💿 in /JCBIndiaLtd Dealer's stamp:

